185

2 E

4-673 b

SUBDIVISION T. 9 S., R. 69 E.

16

<u> </u>	Chains	
	79.92	Intersect the N. bdy. of the township, 16 lks. W. of the
- ( - 1	883 BQ (0)	cor. of secs. 1, 2, 35, and 36. Thence
	1992 - 198 1987 - 194	S. 0° 06' W., on true line bet. secs. 1 and 2.
		Desc. over a general S. slope, 50 ft.
	39.92	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	.adle 3	s2 S1
		1934
		Deposit a granite stone 4x6x6 ins. mkd. with a cross (X), at base of post.
	· · · · · · · · · · · · · · · · · · ·	Continue to desc. S. slope, 10 ft.
	67.77	
	79.92	Cor. of secs. 1, 2, 11, and 12.
	14 68 X •	Land, rolling. Soil, gravelly. Undergrowth, blackbrush, creosote and cacti. No timber.
		No timoer.
	1. <sup>56</sup> 5.95	diam. 'firmly' set, mkd. and witnessed, as described in
	42° - 243 19	Book "A", Group 61 Nevada. N. 0°01' W., bet. secs. 34 and 35.
		Asc. 25 ft. over a gradual S. slope to 40.00 ch. point.
	26.80	Road in bottom of wash, drains SW., bears NE. and SW.
	40.00	Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground and in a mound of stone and earth to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
-	a hear an an	\$34 \$35
1		1934
		dig pits, 18x18x12 ins. N. and S. of post, 3 ft. dist.
ľ.		ABC. 30 ft. over a gradual SW. slope.
	80.00	the ground, for the cor. of secs. 26, 27, 34, and 35, with brass cap mkd.
		T9S R69E S27 S26
i Linear and	a a sa a sa a sa a sa a	\$34 \$35 1974
	• 3 · 40	1934 raise a mound
		of stone, 4 ft. base, 3 ft. high, W. of cor.

U S. GOVERNMENT PRINTING OFFICE: 1931 8---8155