For description of instruments and method of measurement refer to the field notes of T.~10~S.,~R.~69~E., executed during the same period and in conjunction with this township, under Groups 61 and 183 Nevada.

Azimuth determinations were made at frequent intervals during the survey of the township, and bearings were carried by transit angulation and checked by several repetitions. For detailed data pertaining to azimuth determinations on the boundaries of this township, refer to the field notes of the Independent Resurvey of the E. bdy. of T. 12 S., R. 70 E. The E. bdy. of T. 9 S., R. 70 E., was extended from Polaris observation taken at the standard cor. of Ts. 12 S., Rs. 70 and 71 E. and run north on the E. bdys. of Ts. 12, 11 and 10 S., R. 70 E., executed under this same group.

The E. bdy. of T. 9 S., R. 69 E., identical with the W. bdy. of T. 9 S., R. 70 E., was surveyed in 1934 under Group 183 and accepted July 8, 1935.

The geographic position of the SE. cor. of the Township is:

Latitude: 37°06'15"N. Longitude: 114°06'33"W.

From the cor. of Tps. 9 and 10 S., Rs. 70 and 71 E., described in the field notes of T. 10 S., R. 70 E., surveyed under this assignment.

North, bet. secs. 31 and 36.

Over rolling, washed desert land, through low brush.

2.80 Main wash, 40 lks. wide, course NE., asc. 30 ft. on SE. slope.

10.00 | Spur, slopes E., desc. 20 ft. on NE. slope.

18.00 Wash, 1 ch. wide, course SE., asc. 170 ft. on S. slope.

30.90 | Slope changes to SE., cont. to asc.

40.00 Point for the 4 sec. cor. of secs. 31 and 36.

Set an iron post, 30 ins. long, 2 ins. diam.. 20 ins. in the ground, and in a mound of stone, with brass cap mkd.

\$ 36|S 31

Ascend 88 ft.

45.60 Rocky spur, bears SE., desc. 85 ft. on NE. slope.

50.80 Wash, course E., asc. 47 ft. on S. slope.

54.50 Spur, slopes E., desc. 60 ft. on NE. slope.

61.40 Wash, course SE., asc. 250 ft. on S. slope. Enter mountainous land.

72.50 Spur, slopes SE., desc. 90 ft. on NE. slope.

76.00 Wash, course SE., asc. 75 ft. on S. slope.

80.00 Point for the cor. of secs. 25, 30, 31 and 36.

Set an iron post, 30 ins. long, 2 ins. diam.. 3 ins. in the ground to bedrock, and in a mound of stone, with brass cap mkd.