

NORTH BDY., T. 9 S., R. 71 E.

Chains

Land, broken hills.
Soil, rock and gravel and coarse loam.
Undergrowth, joshua, sagebrush, greasewood and cacti.

East, bet. secs. 4 and 33.

Over broken hills. Descend 10 ft.

1.60 Side wash, 15 lks. wide, drains N. 15° E., asc. 180 ft. on broken and rocky NW. slope.

20.00 High rocky spur, slopes N., desc. 450 ft. over E. slope.

37.30 Bull Valley Wash, 1 ch. wide, drains S. for 1 ch., thence S. 80° E., asc. 55 ft. over W. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 33.

Set an iron post, 36 ins. long, 2 ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd..

S 33
 $\frac{1}{4}$ —
S 4
1953

Ascend 65 ft.

46.50 Spur, slopes S., desc. 130 ft. over E. slope.

57.20 Wash, 25 lks. wide, drains S., asc. 400 ft. over broken W. slope.

78.00 Long spur, bears S. 20° W., from N. 75° E.; change to SW. slope.

80.00 Point for the cor. of secs. 3, 4, 33 and 34.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.

T 8 $\frac{1}{2}$ S R 71 E
S 33 S 34
S 4 S 3
T 9 S
1953

Land, broken hills.
Soil, rocky.
Undergrowth, joshua, sagebrush, greasewood and cacti.

East, bet. secs. 3 and 34.

Over broken hills. Ascend 65 ft.

9.00 Side spur, slopes S., desc. 60 ft. over SE. slope.

14.40 Side ravine, drains S., asc. 40 ft. over SW. slope.

17.26 Intersect the Nevada-Utah State line.

Point for the closing cor. of Tps. 8 $\frac{1}{2}$ and 9 S., R. 71 E.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground and in a mound of stone to top, with brass cap mkd.