

420 30

SUBDIVISION OF T. 9 S., R. 71 E.

Chains

T 9 S		UTAH
S 10		
CC		
S 15		
R 71 E		
1953		

From this point the 289 Mi. cor. on the Nevada-Utah State line bears S. $1^{\circ} 07'$ W., 83 lks. dist.

At midpoint on the E. bdy. of sec. 15, on the Nevada-Utah State line.

Point for the $\frac{1}{4}$ sec. cor. of sec. 15.

Set an iron post, 36 ins. long, 2 ins. diam., 26 ins. in the ground and in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$		UTAH
S 15		
1953		

From this point the 289 Mi. cor. on the Nevada-Utah State line bears N. $0^{\circ} 08'$ E., 39.16 chs. dist.

Land, rolling.

Soil, sand, rock and gravel.

Undergrowth, joshua, sagebrush, greasewood and cacti.

From the cor. of secs. 9, 10, 15 and 16.

N. $0^{\circ} 02'$ E., bet. secs. 9 and 10.

Over rolling desert. Over broad ridge-spur, slopes SE.

2.00 Leave top, desc. 10 ft. over NE. slope.

6.50 Scraped road, bears W. and S. 75° E.

29.50 Side draw, drains SE. Ascend 50 ft. to $\frac{1}{4}$ sec. cor.

40.00 Point for the $\frac{1}{4}$ sec. cor. of sec. 9 and 10.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground and in a mound of stone to top, with brass cap mkd.

$\frac{1}{4}$		S 10
S 9		
1953		

Ascend 20 ft.

41.70 Scraped road, bears N. 35° W. and S. 35° E., on broad ridge spur.

50.00 Leave top, desc. 183 ft. over NE. slope of broken land.

65.00 Wash, 20 lks. wide, drains SE., winding. Ascend 82 ft.

70.00 Side spur, bears S. 75° E., about 5 chs. to end. Descend 31 ft.

73.80 Side ravine, drains S. 50° E. Ascend 107 ft.

80.00 Point for the cor. of secs. 3, 4, 9 and 10.