

Resurvey, N. Bdy., T. 11 S., R. 71 E.

Chains

For description of instruments and method of measurement refer to the field notes of T. 10 S., R. 69 E., executed during the same period and in conjunction with this township under Groups 183 and 61, Nevada.

Azimuth determinations were made at frequent intervals during the survey of the township and bearings were carried by transit angle, checked by several repetitions. For detailed data pertaining to azimuth determinations on the bdys. of this township, refer to the field notes of T. 10 S., R. 70 E., executed under this same group.

The State line between Nevada and Utah was originally surveyed by I. E. James, Deputy Surveyor in 1870. It was dependently resurveyed from mile posts 293 to 295 by G. W. Ridgway in 1920 and from mile posts 295 to 300 by Kelvin Winwood in 1936.

Resurvey of the N Bdy., T. 11 S., R. 71 E., Superseding the Survey Executed by Deputy Surveyor W. H. Myrick in 1881

No evidence of the original survey was found.

From the cor. of Tps. 10 and 11 S., Rs. 70 and 71 E., described in the field notes of T. 10 S., R. 70 E., surveyed under this group.

East, bet. secs. 6 and 31.

Over gently rolling desert land. Descend 35 ft.

2.00 Enter large valley, drains S.

2.60 Scraped road, bears N. and S.

3.40 Water course, drains S.

18.00 Leave valley, asc. 90 ft. over W. slope.

22.50 Ridge, bears NW. and SE. Descend 15 ft.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 31.

Set an iron post, 30 ins. long, 2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd:

S 31

$\frac{1}{4}$

S 6

1953

Descend 60 ft.

44.90 Wash, 10 lks. wide, drains S., asc. 72 ft. over SW. slope.

50.50 Descend 85 ft. over SE. slope.

80.00 Point for the cor. of secs. 5, 6, 31 and 32.

Set an iron post, 30 ins. long, 2 ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.