

Subdivision of T. 10 S., R. 71 E.

Chains
21.40 Small spur, slopes SE., desc. over E. slope.
30.90 Side wash, 10 lks. wide, drains S.
39.99 Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 33.
Set an iron post, 30 ins. long, 2 ins. diam., 26 ins. in the ground, with brass cap mkd.

S 28

 $\frac{1}{4}$

S 33

1953

Dig a circular trench, 5 ft. diam., 1 ft. deep and raise a mound of earth around the post to top.

Ascend 27 ft.

45.70 Small spur, slopes SE. Descend 40 ft.
53.70 Side wash, 10 lks. wide, drains S.
56.10 Wash, 30 lks. wide, drains S. Ascend 65 ft. to sec. cor.
65.10 Small spur, bears S.
74.60 Side wash, 10 lks. wide, drains S.
79.98 The cor. of secs. 27, 28, 33 and 34.

Land, gently rolling.
Soil, sand and gravel.
Undergrowth, joshua, sagebrush and greasewood.

East, bet. secs. 27 and 34.

Over gently rolling desert land.

5.40 Side wash, drains S.
10.80 Side wash, drains S.
13.80 Small spur, slopes SE.
24.04 Intersect the Nevada-Utah state line.
Point for the closing cor. of secs. 27 and 34.
Set an iron post, 30 ins. long, 2 ins. diam., 20 ins. in the ground and in a mound of stone to top, with brass cap mkd.

T 10 S

S 27

CC S 34

R 71 E

1953

UTAH

From this point the 298th Mi. cor. of the Nevada-Utah state line bears N. $0^{\circ} 38'$ W., 2 lks. dist., and is monumented with an iron post, 3 ins. diam., 3 ins. above ground, mkd. and witnessed as described in the official record. Both monuments are surrounded by one mound of stone.

At midpoint on the E. bdy. of sec. 34.