## Independent Resurvey of the East Boundary of T. 17 N., R. 52 E.

	The second secon	
	Chains	
		Beginning at the original cor. of Ts. 16 and 17 N., Rs. 52 and 53 E.; the original post or its remains were not recovered. However, the small mound of stone was recovered and was verified and found to be in relative harmony with original corners found to the E., S., and W. No original corners were found to the N.
		At the corner point
		Set an iron post, 3 ft. long, 3 ins. diam., 30 ins. in the ground, for cor. of Ts. 16 and 17 N., Rs. 52 and 53 E., with brass cap mkd.
		T17N R52E R53E S36   S31 S1   S6 T16N 1936
		Raise a mound of stone, 5 ft. base, 3½ ft. high, S. of cor.
		Thence
	-	
		North, bet. secs. 31 and 36.
		Over rolling mountainous land, through scattering timber and dense undergrowth; desc. along canyon bottom.
	7.20	Dry wash, drains S. 40° E. from N. 10° W.; asc. 85 ft. along floor of canyon.
-	21.50	Leave canyon bottom, bears S. 15° E. and N. 15° W.; asc. 46 ft. over a gradual SW. slope.
	26.20	Asc. 180 ft. over an abrupt SW. slope.
	40.00	Point for the ½ sec. cor. of secs. 31 and 36.
	(B)	Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground, and in a mound of stone, $2\frac{1}{2}$ ft. base, 16 ins. high, with brass cap mkd.
	(50)	<del>1</del> / <sub>4</sub>
		s 36   s 31
		1936
To good Transport		No auxiliary accessory.
	40.90	Spur, slopes SE. from W.; desc. 10 ft. along an E. slope of crest of spur.
-	46.80	Leave spur; desc. 142 ft. over a general N. slope.
	53.20	Head of small draw, drains E.; desc. 124 ft. along E. slope.
	55.40	Low spur, slopes E.; desc. 64 ft. over NE. slope.
	59.70	Draw, drains S. 80° E.; asc. 74 ft. over a gentle S. slope.
	73.35	Spur, slopes E. for 10 chs. to foot; desc. 206 ft. over a NE. slope.
	80.00	Point for the cor. of secs. 25, 30, 31 and 36.
Control of the Contro		Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.