

SURVEY OF THE BOUNDARIES OF EUREKA TOWNSITE

Chains

By a preliminary examination on the ground, I ascertained in order to include all contemplated improvements, that this area covers the following légal subdivisions:

SW $\frac{1}{4}$ NW $\frac{1}{4}$ and W $\frac{1}{2}$ SW $\frac{1}{4}$ of Section 13;
 SE $\frac{1}{4}$ NE $\frac{1}{4}$ and SE $\frac{1}{4}$ of Section 14;
 NW $\frac{1}{4}$ NE $\frac{1}{4}$ and E $\frac{1}{2}$ NE $\frac{1}{4}$ of Section 23;
 and the W $\frac{1}{2}$ of the NW $\frac{1}{4}$ Section 24,

all in T. 19 N., R. 53 E., M.D. Mer., Nevada

Subdivision of Section 13.

Begin at the $\frac{1}{4}$ sec. cor. of secs. 13 and 24 described in the official records of T. 19 N., R. 53 E.

Thence

N. 0° 01' W., on a random line on N. and S. center line of sec. 13.

40.00 Set temp. center $\frac{1}{4}$ sec. cor.

60.00 Set temp. center N. 1/16 sec. cor.

80.00 Intersect the N. bdy. of sec. 13 at a point 1 lk. W. of $\frac{1}{4}$ sec. cor. of secs. 12 and 13, described in the official records of T. 19 N., R. 53 E.

Thence

S. 0°00' 30" E., on true N. and S. center line of sec. 13.


Over rolling mountainous land, through scattering timber, and dense undergrowth; desc. 6 ft. along a W. slope.

7.30 Wash, course N. 20° E.

Telephone line, bears E. and W.; asc. 128 ft. over a broken N. slope to 20.00 chs.

16.90 Trail, bears E. and W.

20.00 Set an iron post, 3 ft. long, 1 in. diam., 9 ins. in the ground to bedrock, with a limestone, 3x3x5 ins., mkd. (X), deposited at the base, and in a large mound of stone to top for center N. 1/16 sec. cor. of sec. 13, with brass cap mkd.



Asc. 43 ft.

25.00 Slope changes; asc. 53 ft. along a gentle W. slope.

34.70 Head of wash, course W.; asc. 83 ft. over a broken N. slope.

40.00 Set a hub for temp. adjusted center $\frac{1}{4}$ sec. cor.; asc. 113 ft.