

Survey of a Portion of the East Boundary of T. 19 N., R. 53 E.

Chains	
2.50	Wash, course NW.; asc. 65 ft. over a rocky SW. slope.
8.90	Spur, slopes W.; desc. 75 ft. over a rocky NW. slope.
16.20	Wash, course N. 60° W.; desc. 50 ft. over a rocky W. slope.
24.80	Slope changes; desc. 230 ft. over a rocky NW. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 18. Set an iron post, 3 ft. long, 1 in. diam., 15 ins. in the ground to bedrock, with a limestone, 2x5x6 ins., mkd. (X), deposited at the base, and in a mound of stone, 3 ft. base, 21 ins. high, with brass cap mkd. $\begin{array}{c} \frac{1}{4} \\ S\ 13 \mid S\ 18 \\ 1935 \end{array}$ Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. Desc. 255 ft. over a NW. slope.
71.90	Wash, 15 lks. wide, with sloping banks, 6 ft. high, course NW.; desc. 95 ft. along W. slope.
80.00	Point for the cor. of secs. 12 and 13, only. Set an iron post, 3 ft. long, 2 ins. diam., 17 ins. in the ground to bedrock, and with a limestone, 2x3x3 ins., mkd. (X), deposited at the base, and in a mound of stone, 2 $\frac{1}{2}$ ft. base, 19 ins. high, with brass cap mkd. $\begin{array}{c} T19N \\ R53E\ R54E \\ \frac{S12}{S13} \mid S18 \\ 1935 \end{array}$ Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. Land, broken mountainous. Soil, shallow, sandy clay, with integrated coarse gravel and embedded washed boulders. Timber, a few scrub juniper; undergrowth, sagebrush, buckbrush, service bushes, with a fine stand of native grasses.
2.67	North, along the E. bdy. of sec. 12, and continuing along W. bdy. of sec. 18. Over rolling mountainous land, through dense undergrowth; desc. 15 ft. The original cor. of secs. 7, 12, 13 and 18, which is monumented with a lava stone, 6x3x12 ins. above the ground, firmly set, mkd. and witnessed as described in the official record. As this cor. will no longer function for secs. of T. 19 N., R. 53 E., it is now remonumented to refer to secs. 7 and 18, T. 19 N., R. 54 E. only. At the corner point