115

.

Survey of the South Boundary of T. 19 N., R. 53 E.

16

	Chains	
	41.80	Low flat spur, slopes N.; thence across shallow swale, draining N. 20° W.
	44.30	Head of wash, drains N. 60° W.; asc. along a general N. slope.
	54.30	Top of ascent, bears NW. and SE.; desc. 55 ft. along head of swale, draining N. 30° W.
	70.30	Low flat spur, slopes N.; desc. 75 ft. over a NW. slope.
	79.40	A safe place for witness cor. of lots 10 and 11, sec. 31.
		Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock, with a limestone, 3x4x6 ins., mkd. (X), deposited at the base, and in a mound of stone, 4 ft. base, 30 ins. high, with brass cap mkd.
		$\begin{array}{c} S 31 \\ W 10 11 \\ C \end{array}$
		1936
	80.00	True point for lot corner falls on exposed boulder at an unsuitable site for a permanent monument.
·	85.25	Intersect the E. bdy. of sec. 1, T. 18 N., R. 52 E. at point for closing cor. of Ts. 18 and 19 N., R. 53 E.
		Set an iron post, 3 ft. long, 3 ins. diam., 20 ins. in the ground to bedrock, and in a mound of stone, $2\frac{1}{2}$ ft. base, 16 ins. high, with brass cap mkd.
		$ \begin{array}{c} \text{T19N}\\ \text{T18N}  \text{R53E}\\ \text{S1}  \text{S31}\\ \text{R52E}  \text{S6} \end{array} $
		T18N 1936
		from which
		A mahogany, 5 ins. diam., bears N. 55½° E., 19½ lks. dist., mkd. BT only.
	•	A mahogany, 4 ins. diam., bears S. 46½° E., 161 1ks. dist., mkd. BT only.
	•	From this corner, the cor. of Ts. 18 and 19 N., R. 52 E., which is monumented with an iron post, 3 ins. diam., set, mkd. and witnessed as described in the field notes of the independent resurvey of the E. bdy. of T. 18 N., R. 52 E., executed concurrently under this same survey group, bears North, 14.92 chs. dist.
		Land, rough mountainous. Soil, sandy shallow, mixed with decomposed limestone, shale, basalt, granite, and quartzite, with many basalt outcroppings. Timber, mahogany, juniper, and pinon; undergrowth, sagebrush, buckbrush, and a fine stand of native grasses.
		^