Independent Resurvey, Portion of the South Boundary, T. 20 N., R. 52 E.

Chains	
61.60	Old unimproved road, bears N. 60° W. and S. 60° E.
78.10	Draw, drains N. 20° E.; asc. 15 ft. along N. slope.
80,00	Point for the cor. of secs. 35 and 36.
	Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.
	T20N R52E S35 S36 S 1
	T19N R52E 1937
	Raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.
	From this corner, the original cor. of secs. 1, 2, 35 and 36, which is monumented with a granite stone, 17x11x10 ins., firmly set, mkd. and witnessed as described in the official record, bears N. 34° 13' W., 13.38 chs. dist. I destroy this corner and its accessories.
	Land, part hilly, part rough mountainous.
	Soil, shallow, coarse rocky loam and clay. Timber, pinon, juniper, and scrub mahogany; undergrowth, sagebrush, buckbrush, and shadscale.
	Independent Resurvey, East Boundary of T. 19 N., R. 52 E.
, and a second s	Superseding the Survey Executed by Bridges and Eaton, Deputy Surveyors, in 1879.
*	Note: Diligent search was made for evidence of the original survey of this line, but no original corners were recovered except the 2 sec. cor. of secs. 1 and 6, which I destroy as hereinbefore explained.
	Beginning at the reestablished cor. of Ts. 18 and 19 N., R. 52 E., which is monumented with an iron post, 3 ins. diam., firmly set, mkd. and witnessed as described in the field notes of the independent resurvey of the east boundary of T. 18 N., R. 52 E., executed concurrently under this same survey group.
	North, along the E. bdy. of sec. 36.
	Over broken hilly land, through medium dense timber and undergrowth; asc. slightly along a SW. to W. slope.
3.00	Draw, drains NW.
5.70	Spur, slopes S. 80° W.; desc. slightly over NW. slope.
15.40	Draw, drains S. 40° W., from branches from S. 80° E. and N. 40° E.; asc. 50 ft. over SE. slope.
23.20	Spur, slopes S. 70° W.; continue descent over gradual NW. slope.
29.60	Draw, drains S. 80° W.; asc. 50 ft. over gradual SE. slope.