Survey of the Subdivision of T. 19 N., R. 53 E.

Chains	
	A juniper, 4½ ins. diam., bears S. 13½° W., 17 1ks. dist., mkd. ½ S10 BT.
	Desc. rolling W. slope.
47.10	Leave timber, bears N. and S. and continue through medium dense low undergrowth.
53.40	Unimproved road, bears N. 10° W. and S.
56.00	Shallow drain, course NW.
80.04	The cor. of secs. 3, 4, 9 and 10.
	Land, rolling and broken. Soil, shallow gravelly to coarse rocky loam. Timber, juniper and pinon; undergrowth, shadscale, sagebrush, and buckbrush.
	N. 0° 02'.W., bet. secs. 3 and 4.
	Over rolling land, through medium dense low undergrowth.
33.97	Intersect the south boundary of sec. 33, T. 20 N., R. 53 E., at point for closing cor. of secs. 3 and 4.
	Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground to solid rock, over a cross (X), and in a mound of stone, 3 ft. base, 16 ins. high, with brass cap mkd.
	T20N R53E
,	<u>\$33</u> .
	. S4 S3 T19N
	CC
	1937
	Raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.
	From this corner, the cor. of secs. 33 and 34, T. 20 N., R. 53 E., which is monumented with an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record, bears East, 20.85 chs. dist.
	Land, rolling. Soil, shallow, gravelly clay loam. Timber, juniper; undergrowth, sagebrush, shadscale, and buckbrush.
	At the point for the N. ½ sec. cor. of sec. 3, at midpoint bet. the NE. and NW. cors. of sec. 3.
	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a basalt rock, $4x3x1\frac{1}{2}$ ins., mkd. X, deposited at the base, with brass cap mkd.
	½ S 3
	1937
	No auxiliary accessory.