

Survey of the Subdivision of T. 19 N., R. 53 E.

Chains	
15.40	Spur, slopes S. 50° E.; desc. 50 ft. over SW. slope.
22.00	Drain, course S. 60° E.; asc. 290 ft. over abrupt NE. slope.
40.00	<p>Point for the ¼ sec. cor. of secs. 30 and 31, on crest of main divide bearing N. and S.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., over a cross, X, cut on exposed ledgerock, and in a mound of stone, 6 ft. base, 36 ins. high, with brass cap mkd.</p> <div><div>¼</div><div><div>S 30</div><div>S 31</div><div>1937</div></div></div> <p>No auxiliary accessory.</p> <p>This ¼ sec. cor. is situated on crest of main divide ridge, bears N. and S.</p> <p>From this corner, U. S. Mineral Monument No. 9, which is monumented with a native pinon post, 6 ins. square, and firmly set, projecting 3 ft. above a substantial mound of stone, faintly scribed U S M M on S. face, bears S. 24° 12' E., 0.45 chs. dist.</p> <p>Desc. 130 ft. over W. slope.</p>
46.60	Head of small draw, drains SW.
52.10	Small spur, slopes SW.; desc. 100 ft. over W. slope.
55.00	Small draw, drains SW.
67.40	Spur, slopes SW.; desc. 80 ft. over W. slope.
77.00	Main draw, drains S.
80.00	<p>Point for the cor. of lots 4 and 5 of sec. 31 only.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground, over a cross, X, cut on solid rock, and in a mound of stone, 4 ft. base, 30 ins. high, with brass cap mkd.</p> <div><div>S 30</div><div>5 4</div><div>S 31</div><div>1937</div></div> <p>No auxiliary accessory.</p>
81.60	Spur, slopes SW.; desc. W. slope.
85.07	<p>Intersect the E. bdy. of sec. 36, T. 19 N., R. 52 E., at point for closing cor. of secs. 30 and 31.</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., 4 ins. in the ground, over a cross, X, cut on solid rock, and in a mound of stone, 4 ft. base, 32 ins. high, with brass cap mkd.</p> <div><div>T19N</div><div>R52E R53E</div><div>S36 S30</div><div>S31 CC</div><div>1937</div></div>