

Survey of the Subdivision of T. 19 N., R. 53 E.

Chains	
77.40	Spur, slopes N. 30° E.; desc. along steep N. slope.
84.91	<p>Intersect the E. bdy. of sec. 25, T. 19 N., R. 52 E., at point for closing cor. of secs. 19 and 30.</p> <p>Set an iron post, 3 ft. long, 2 ins. diam., over a cross, X, cut on exposed ledge, and in a mound of stone, 6 ft. base, 36 ins. high, with brass cap mkd.</p> <div><div>T19N</div><div>R52E R53E</div><div>S25 S19 S30 CC</div><div>1937</div></div> <p>from which</p> <p>A pinon, 5 ins. diam., bears N. 70° E., 82 lks. dist., mkd. BT only.</p> <p>A mahogany, 4 ins. diam., bears S. 34¼° E., 83 lks. dist., mkd. BT only.</p> <p>The cor. of secs. 24 and 25, T. 19 N., R. 52 E., bears North, 14.88 chs. dist.</p> <p>Land, rough mountainous. Soil, shallow coarse rocky loam. Timber, juniper, pinon, and mahogany; undergrowth, sagebrush, shadscale, serviceberry, and deer brush.</p>
	<p>At the point for the W. ¼ sec. cor. of sec. 30, at midpoint bet. the NW. and SW. cors. of sec. 30.</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to solid rock, with a limestone, 4x6x3 ins., mkd. X, deposited at the base, and in a mound of stone, 4 ft. base, 24 ins. high, with brass cap mkd.</p> <div><div>¼</div><div>S 30</div><div>1937</div></div> <p>No auxiliary accessory.</p> <p>From this corner, the E. ¼ sec. cor. of sec. 25, T. 19 N., R. 52 E., bears North, 14.90 chs. dist.</p>
	<p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0° 04' W., bet. secs. 19 and 20.</p> <p>Over rough broken hilly land, through medium heavy second growth timber and dense undergrowth; desc. 60 ft. over NW. slope.</p>
5.40	Draw, drains E.; asc. 150 ft. over a broken S. slope.
12.70	Spur, slopes SE.