

377

Survey of the Subdivision of T. 19 N., R. 53 E.

Chains	
60.20	Unimproved road, bears N. 40° W. and S. 40° E.
80.02	The cor. of secs. 7, 8, 17 and 18. Land, rolling. Soil, gravelly to coarse rocky loam. Timber, pinon and juniper; undergrowth, sagebrush and shadscale.
	West, bet. secs. 7 and 18.
	Over rolling land, through medium dense undergrowth; asc. gentle NE. slope.
14.40	Unimproved road, bears N. 60° W. and S. 80° E.; asc. rolling NE. slope.
18.00	Minor spur, slopes N. 60° E.; desc. NW. slope.
19.00	Head of draw, drains NW.
25.20	Unimproved road, bears NE. and SW.; asc. 130 ft. along crest of small spur sloping E.
34.30	Spur, slopes E. from S. 60° W.; asc. along NE. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18. Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.
	$\frac{1}{4}$ S 7 S 18 1937
	Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
	Cor. situated in head of draw, drains N. 60° E.
	Asc. 220 ft. over abrupt, rocky E. slope.
49.10	Main spur, slopes N. 30° W.; desc. 140 ft. over rocky SW. slope.
58.20	Spur, slopes S. 60° W.; desc. 190 ft. over broken W. slope.
68.30	Bottom of main draw, drains N. 30° W.
69.30	Small spur, slopes N.
71.20	Small draw, drains N.
80.00	Spur, slopes N. 60° E.; desc. NW. slope.
81.50	Draw, drains N. 60° E.
84.76	Intersect the E. bdy. of sec. 13, T. 19 N., R. 52 E., at point for closing cor. of secs. 7 and 18. Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a granite stone, 6x6x3 ins., mkd. X, deposited at the base, with brass cap mkd.