

Survey of the Subdivision of T. 19 N., R. 53 E.

Chains

Raise a mound of stone, 3 ft. base, 1½ ft. high, N. of cor.

45.60 Unimproved road, bears N. 80° W. and S. 80° E.

56.00 Wide flat spur, slopes NE. from S.; desc. gentle NW. slope.

57.90 Unimproved road, bears N. 60° E. and S. 20° W.

61.30 Main draw, drains N. 60° E.; asc. 80 ft. over E. slope.

84.72 Intersect the E. bdy. of sec. 12, T. 19 N., R. 52 E., at point for closing cor. of secs. 6 and 7.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a basalt rock, 4x3x3 ins., mkd. X, deposited at the base, with brass cap mkd.

T19N
R52E R53E
S12 | S6 — CC
 | S7
1937

No auxiliary accessory.

From this corner, the cor. of secs. 1 and 12, T. 19 N., R. 52 E., bears North, 14.84 chs. dist.

Land, rolling.

Soil, fine gravelly to medium coarse rocky loam.

Timber, pinon; undergrowth, sagebrush, shadscale, and yellow top.

At the point for the W. ¼ sec. cor. of sec. 7, at midpoint bet. the NW. and SW. cors. of sec. 7.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with a granite rock, 4x4x2 ins., mkd. X, deposited at the base, with brass cap mkd.

| ¼
| S 7
1937

No auxiliary accessory.

From this corner, the E. ¼ sec. cor. of sec. 12, T. 19 N., R. 52 E., bears North, 14.84 chs. dist.

From the cor. of secs. 5, 6, 7 and 8.

N. 0° 04' W., bet. secs. 5 and 6.

Over rolling land, through medium dense undergrowth.

7.60 Shallow drain, course E.

34.40 Unimproved road, bears N. 60° E. and S. 60° W.