

Survey of the Subdivision of T. 19 N., R. 53 E.

Chains

34.52

Intersect the S. bdy. of sec. 31, T. 20 N., R. 53 E., at point for closing cor. of secs. 5 and 6.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with brass cap mkd.

T20N R53E  
S31  
S6|S5  
C C  
T19N  
1937

Raise a mound of stone, 2 ft. base, 1½ ft. high, S. of cor.

From this corner, the cor. of secs. 31 and 32, T. 20 N., R. 53 E., which is monumented with an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record, bears S. 89° 10' E., 19.83 chs. dist.

Land, rolling.  
Soil, gravelly to rocky clay loam.  
Timber, pinon; undergrowth, sagebrush and buckbrush.

At the point for the N. ¼ sec. cor. of sec. 5, at midpoint bet. the NE. and NW. cors. of sec. 5.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

¼ S 5  
1937

Raise a mound of stone, 2 ft. base, 1½ ft. high, S. of cor.

From this corner, the cor. of secs. 31 and 32, T. 20 N., R. 53 E., which is monumented with an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the official record, bears N. 89° 43' W., 20.21 chs. dist.

At the point for the N. ¼ sec. cor. of sec. 6, and at a point 40.00 chs. westing from the closing cor. of secs. 5 and 6.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.

¼ S 6  
1937

Raise a mound of stone, 2 ft. base, 1½ ft. high, S. of cor.

From this corner, the S. ¼ sec. cor. of sec. 31, T. 20 N., R. 53 E., which is monumented with an iron post, 1 in. diam., firmly set, mkd. and witnessed as described in the official record, bears S. 89° 10' E., 16.07 chs. dist.

From this same corner, the cor. of Ts. 20 N., Rs. 52 and 53 E., bears N. 89° 10' W., 17.04 chs. dist.