

Dependent Resurvey, Portion of the Subdivision, T. 19 S., R. 55 E.

Chains

Reestablishment of the Survey Executed by
Theodore Binge, Deputy Surveyor, in 1881.

The original cor. of secs. 8, 9, 16 and 17 is monumented with a pinon post, 3 ins. diam., 30 ins. long, mkd. TXLXS RLVE SIX on NE. face, SXIII on NW. face, SXVII on SW. face, and illegible scribe marks on SE. face.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with brass cap mkd.

T19S	R55E
S8	S9
S17	S16
1942	

Deposit the old wooden post alongside the iron post.

from which

Original bearing trees

A pinon, 10 ins. diam., bears N. 56° E., 13 lks. dist., mkd. TXIXS RLVE SIX BT.

A pinon, 10 ins. diam., bears S. $69\frac{1}{4}^{\circ}$ E., 82 lks. dist., with illegible marks; without disturbing the original marks, add the marks T19S R55E S16 BT.

A pinon, 15 ins. diam., bears S. 83° W., 74 lks. dist., mkd. S LVE SXVII with other marks overgrown.

A pinon, 5 ins. diam., bears N. $6\frac{1}{2}^{\circ}$ W., 27 lks. dist., mkd. TXIXS RLVE SXVI BT.

N. 1° 31' E., bet. secs. 8 and 9.

Asc. 300 ft. over general S. to SW. slope.

30.00 Spur, slopes S. 60° W.; desc. 50 ft. along general W. slope.

35.00 Asc. slightly along general W. slope.

41.55 Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1 in. diam., over a cross (X) cut in surface rock, supported in a mound of stone, 4 ft. base, 3 ft. high, with brass cap mkd.

	$\frac{1}{4}$	
S 8		S 9
1942		

from which

A pinon, 5 ins. diam., bears S. 27° E., 106 lks. dist., mkd. $\frac{1}{4}$ S9 BT.

A pinon, 6 ins. diam., bears S. 62° W., 48 lks. dist., mkd. $\frac{1}{4}$ S8 BT.

Desc. 100 ft. along general W. slope.