


Subdivision of T. 11 N., R. 59 E.

- Chains  
 34.37 Intersect line 3-4 of HES No. 189, Cor. No. 3, bears N. 29° 23' E., 6.56 chs. dist.; a limestone, 10x12x8 ins. set, mkd. and witnessed as described in the official record.
- 35.10 Leave dense undergrowth, enter cultivated field, bears N. 26° E. and S. 26° W.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.




raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

From this  $\frac{1}{4}$  sec. cor., the top of a reservoir dam, at the outlet, bears N. 39° 37' E., 32.90 chs. dist.

- 40.50 Bottom of valley wash, very shallow, course S. 25° W.
- 42.00 Leave cultivated field, enter dense undergrowth, bears N. 9° E. and S. 9° W.
- 44.40 Irrigating ditch, 2 lks. wide, 1 ft. deep, course S. 13° W.
- 44.90 Ungraded road, bears N. 18° E. and S. 18° W.; asc. 50 ft.
- 51.26 Intersect line 1-2 of HES No. 189, Cor. No. 2, bears N. 35° 28' E., 19.57 chs. dist.; a limestone, 12x10x10 ins., set, mkd. and witnessed as described in the official record.
- 51.30 Wire fence, bears N. 37° E. and S. 37° W.; asc. 100 ft.
- 61.00 Gulch, course SE.; asc. 240 ft. over rocky SE. slope.
- 73.30 Top of spur, projects SE.; desc. 60 ft. over W. slope.
- 77.60 Intersect the W. bdy. of Tp.

Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground to bedrock and in a mound of stone to top, for closing cor. of secs. 7 and 18, with brass cap mkd.



from which

A forked juniper, 6 ins. diam., bears N. 5° E., 196 lks. dist., mkd. T11N R59E S7 CC BT.

A pinon pine, 8 ins. diam., bears S. 26° E., 299 lks. dist., mkd. T11N R59E S18 CC BT.

The cor. of secs. 12 and 13, T. 11 N., R. 58 E., bears North, 4.38 chs. dist.

Land, mountainous, except about 20.00 chs. in the small narrow valley, which is rolling land.  
 Soil, sandy, gravelly and rocky in mountainous land; 4th rate.  
 The soil, in the valley floor is fine light sand and mostly free