

Survey of the North  $\frac{1}{2}$  of the West Boundary, T. 11 N., R. 58 E.

Chains

The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of T. 11 N., R. 58 E., originally established by Monroe and Bateman, Deputy Surveyors, in 1873, is monumented with a limestone, 6x9x18 ins., loosely set in the ground, and marked with 3 grooves on the N. and S. faces.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with brass cap mkd.

T11N	
R57E	R58E
S13	S18
S24	S19
1941	

Deposit the old corner stone at the base of the iron post, and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

North, bet. secs. 13 and 18.

Over gently rolling land, draining generally to the SW.

8.80 Wash, course SW.

25.80 Wash, course SW.

27.50 Draw, drains S.  $10^{\circ}$  W., irregularly from the N.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 13 and 18.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.

S 13		S 18
$\frac{1}{4}$		
1942		

from which

A juniper, 6 ins. diam., bears N.  $12^{\circ}$  W., 202 lks. dist., mkd.  $\frac{1}{4}$  S13 BT.

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

48.30 Desc. 60 ft. over steep NW. slope.

52.50 Narrow arroyo at foot of steep descent.

54.00 Watercourse in arroyo, course S.  $40^{\circ}$  W.

55.50 Road, bears irregularly NE. and SW.

60.00 Asc. 125 ft. over steep SE. slope.

65.30 Crest of steep ascent; cross rolling land, draining to SW.

80.00 Point for the cor. of secs. 7, 12, 13 and 18.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with brass cap mkd.

T11N	
R57E	R58E
S12	S7
S13	S18
1942	