

Dependent Resurvey of the Third Latitudinal Section Line, through
Township 11 North, Range 58 East

Chains

Reestablishment of the Survey Executed by
Monroe and Bateman, Deputy Surveyors, in 1873.

Beginning at the reestablished cor. of secs. 13 and 24, on the E. bdy. of the township, monumented with an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the field notes of T. 11 N., R. 59 E., this group.

S. 89° 51' W., bet. secs. 13 and 24.

Over mountainous land, through scattering timber and dense undergrowth.

0.60 Ravine, course S.; asc. 225 ft. over rocky SE. slope.

14.90 Top of spur, slopes S. for a distance of 5.00 chs., thence projects SW.; desc. 160 ft. over rocky SW. slope.

27.00 Gulch, course S. 15° W.; asc. 15 ft.

34.30 Top of spur, projects SW.; desc. 110 ft. over rocky NW. slope.

39.95 The original $\frac{1}{4}$ sec. cor. of secs. 13 and 24, monumented with a limestone, 5x9x15 ins., loosely set in ground, dimly mkd. $\frac{1}{4}$ on N. face.

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ $\frac{S\ 13}{S\ 24}$
1941

Deposit the old corner stone at the base of the iron post and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.

N. 89° 48' W., beginning new measurement.

Desc. 65 ft. over a N. slope.

7.90 Head of drain, course N.; asc. 30 ft.

12.80 Point of spur, slopes N.; desc. 150 ft. over NW. slope; leave scattering timber, bears N. and S.

22.40 Base of abrupt descent, bears NE. and SW.; desc.

22.70 Ravine, course S. 70° W.; asc. 10 ft.

23.60 Road, unimproved, bears N. 60° E. and S. 35° W.

27.00 Wash, course S. 20° W.; asc.

37.00 Top of low spur, slopes S.; desc. 5 ft.

39.58 The original cor. of secs. 13, 14, 23 and 24, which is marked by a greatly decayed juniper post, 2x2 ins. square and 2 $\frac{1}{2}$ ft. long, lying on the ground alongside a mound of earth; the markings on the post are nearly obliterated. This corner is now remonumented to refer to secs. 23 and 24 only.

At the corner point