

407

Township 27 North, Range 57 East

Chains				
2nd	Direct	9:43:43	45° 57'	79° 01'
"	Reversed	9:46:50	47° 04'	77° 40'
	Mean	9:45:16	46° 30' 30"	78° 20' 30"
3rd	Direct	9:44:38	46° 06'	78° 03'
"	Reversed	9:45:44	46° 52'	78° 39'
	Mean	9:45:11	46° 29'	78° 21'

Mean true bearing of flag S. 1° 10' 10" W.

The true bearings of lines extending N., S., E. and W. from this township corner are determined by deflection from the above reference flag.

Retracement and Partial Dependent Resurvey, Portion of the East Boundary, T. 27 N., R. 57 E.

Partial Reestablishment of the Survey Executed by Hatch and Eaton, Deputy Surveyors, in 1869, under Contract No. 32.

Beginning at the point for the original cor. of secs. 19, 24, 25 and 30, on the E. bdy. of T. 27 N., R. 57 E., which is monumented with an iron post, 3 ins. diam., firmly set, extending 6 ins. above the surface, with brass cap mkd. around the outside edge of the brass cap: U.S. DEPT. OF AGRICULTURE, in the upper semicircle, and BIOLOGICAL SURVEY in the lower semicircle; with the regular penalty indenture of \$250. for removal in a circular form in the same manner as the General Land Office Survey iron post caps; with further markings, on the brass cap

4
T27N
R57E R58E
S24 | S19
S25 | S30
1936

This cor. is surrounded by a flat mound of stone, 2½ ft. diameter.

This cor. was verified by investigation and found that it was reestablished at the original position by the Biological Survey in 1936.

From this corner, the point for the original E. 1/16 sec. cor. of secs. 24 and 25, bears West, 20.00 chs. dist. This 1/16 sec. cor. is monumented with an iron post, 1 in. diam., 12 ins. above ground, surrounded by a mound of stone, 2½ ft. diam., 1 ft. high, believed to be a perpetuation of the original corner position.

Thence, from the cor. of secs. 19, 24, 25 and 30.

N. 0° 35' E., bet. secs. 19 and 24.

Over rolling land, through dense undergrowth, over land which shows evidence of having been cultivated at some time in the past.

40.00

Point for the ¼ sec. cor. of secs. 19 and 24, at record distance; there is no remaining evidence of the original corner. Corner not remonumented. This point for ¼ sec. cor. falls within former C.C.C. campsite.

Asc. 200 ft. along gently rolling E. slope.