

426

Dependent Resurvey, Portion of the North Boundary, T. 28 N., R. 57 E.

Chains

38.20

The original cor. of Ts. 28 and 29 N., Rs. 56 and 57 E., which is monumented with a granite stone, 6x10x10 ins. above ground, firmly set, marked and witnessed as described in the official record. Alongside this stone is a quartzite stone, 10x8x8 ins. above ground, firmly set and marked 1-HES-230 on SW. face.

At the corner point, and without disturbing the HES cor.

Set an iron post, 3 ft. long, 3 ins. diam., 12 ins. in the ground to bedrock, with brass cap mkd.

T29N
R56E R57E
S36 | S31
S1 | S6
T28N
1944

Deposit the old corner stone at the base and raise a mound of stone, 2½ ft. base, 24 ins. high, around the iron post.

From this corner:

The SE. cor. of T. 28 N., R. 56 E., bears S. 1° 16' 40" E., 476.80 chs. dist. (Calculated tie.)

Cor. No. 3 of HES 193, bears S. 0° 26' E., 180.16 chs. dist. (Calculated tie.)

Elevation of this corner, approximately 6030 ft.

Land, mountainous.

Soil, sandy loam to gravelly and rocky.

Timber, scattering aspen; undergrowth, sagebrush and grass.

Survey of the South Boundary, T. 28 N., R. 57 E.

Beginning at the reestablished cor. of Ts. 27 and 28 N., Rs. 57 and 58 E., described in the field notes of the retracement and partial dependent resurvey of a portion of the E. bdy. of T. 27 N., R. 57 E., executed concurrently under this same survey Group.

West, bet. secs. 1 and 36.

Over mountainous land, through scattering timber and dense undergrowth; desc. slightly.

1.00 Wire fence, bears N. 20° E. and S. 20° W.

2.50 Head of small wash, course S. 60° E.

4.20 Head of small wash, drains S. 25° E.; asc. 460 ft. over a general SE. slope.

33.70 Steep spur, falls N. 60° E.; thence asc. 25 ft. along a N. slope.

40.00 Point for the ¼ sec. cor. of secs. 1 and 36.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap mkd.

¼ S 36
S 1
1944

from which

A pinon, 2½ ins. diam., bears N. 69½° E., 70 lks. dist., mkd. ¼ S36 BT.

A pinon, 6 ins. diam., bears S. 15¼° W., 203 lks. dist., mkd. ¼ S1 BT.