

## Township 28 North, Range 58 East

## Chains

The survey of the south, north and east boundaries and the subdivision of T. 28 N., R. 58 E. was made by A. J. Hatch and J. H. Eaton, Deputy Surveyors, in 1869. In 1924 the boundaries of sections 12, 13 and 14 were dependently resurveyed and original surveys extended across sections 1, 2, 3, 11, 12, 13 and 14 to cover all area of the bed of Franklin Lake lying east of the center or partition line of the former lake, by Carl S. Swanholm, Cadastral Engineer, under Group No. 99.

The following field notes are those of a dependent resurvey of a portion of the south boundary and of the subdivision of T. 28 N., R. 58 E.

For a description of surveying instruments and equipment used, tests of instruments, and explanation of methods of determining true meridian, etc., see field notes entitled "Retracement and Partial Dependent Resurvey of Portions of the East and West Boundaries of T. 27 N., R. 57 E.", executed concurrently under this same Group.

The geographic position of the southwest corner of the township, determined by scaling from U.S.G.S. Topographic Quadrangle Sheet "Jiggs", 1934, is latitude  $40^{\circ} 15' 29''$  N., and longitude  $115^{\circ} 29' 21''$  W.

## Dependent Resurvey, Portion of the South Boundary, T. 28 N., R. 58 E.

Reestablishment of the Survey Executed by Hatch and Eaton, Deputy Surveyors, in 1869, under Contract No. 32.

From the reestablished cor. of Ts. 27 and 28 N., Rs. 57 and 58 E., described in the field notes of the retracement and partial dependent resurvey of a portion of the E. bdy. of T. 27 N., R. 57 E., executed concurrently under the current survey Group.

S.  $89^{\circ} 53'$  E., bet. secs. 6 and 31.

Over rolling mountainous land, through dense undergrowth; desc. 180 ft. over E. slope.

38.80

Point for the  $\frac{1}{4}$  sec. cor. of secs. 6 and 31, at record distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\frac{1}{4} \begin{array}{r} S 31 \\ S 6 \\ 1944 \end{array}$$

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor.

From this corner, Cor. No. 4 of Homestead Entry Survey No. 191, bears N.  $51^{\circ} 30'$  W.; 6.77 chs. dist., monumented with a limestone, 10x12x4 ins. above ground, firmly set, mkd. and witnessed as described in the official record; except that all trace of the pits have disappeared.

Desc. gradually 80 ft. along E. slope, to county road.

60.80

Telephone line, bears N.  $15^{\circ}$  E. and S.  $15^{\circ}$  W.

63.50

Improved gravel County road of Ruby Valley, bears N.  $15^{\circ}$  E. and S.  $15^{\circ}$  W.; desc. gradually 30 ft.