

RETRACEMENT

SIXTH STANDARD PARALLEL NORTH, THROUGH RANGES 67, 68, 69 AND 70 E.

Chains

REESTABLISHMENT OF SURVEYS
EXECUTED BY PREBLE AND THOBURN, U.S. DEPUTY SURVEY-
ORS, IN 1881, UNDER CONTRACT NO. 130.

Random Line.

From the standard cor. of secs. 34 and 35, on S. bdy. of
T. 31 N., R. 67 E., which is an iron post, 2 ins. diam.,
12 ins. above ground, with brass cap marked

S C
T 31 N R 67 E

S 34 | S 35

1935

18x18x12 ins., N., E., and W. of post, 3 ft. dist. with pits,

This post was set at the time of the investigation survey,
in 1935; in the place of the original cor. post, which is
described as a post, 4 ins. square, 1 ft. above ground.

Thence East with retracements along the 6th Stan. Par.
N., through Rs. 67, 68, 69, and 70 E., searching for
original cors. and setting temp. points at regular 40.00
chs. dist. intervals. After diligent search, no cors.
were found.

1407.38 Intersect Nevada-Utah Boundary Line, 34.12 chs. N. of the
reestablished standard closing cor. of Tps. 30 and 31 N.,
Rg. 70 E., described in field notes of T. 31 N., R. 70 E.,
this group.

Therefore, the course of this line is S. 88° 37' E. and
its length is 1407.79 chs.

True Line

DEPENDENT RESURVEY
SIXTH STANDARD PARALLEL NORTH, THROUGH RANGE 69 E.

At a point 640.16 chs. S. 88° 37' E. of the standard cor.
of secs. 34 and 35, T. 31 N., R. 67 E., heretofore de-
scribed.

Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the
ground, to bedrock and in a mound of stone to top, for
standard cor. of T. 31 N., Rs. 68 and 69 E., with brass
cap marked

S C
T 31 N
R 68 E | R 69 E
S 36 | S 31

1936

from which

A pine, 3 ins. diam., bears N. 63° W., 434 lks.
dist., marked B T.