

## EAST BOUNDARY OF T. 31 N., R. 68 E.

Chains	
40.00	Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground to bedrock, with a granite stone 8x5x6 ins.; marked X deposited at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of sec. 12 only, with brass cap mkd.
	$\frac{1}{4}$   S 12   1936
	Ascend 90 ft. over broken land.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground to bedrock, and in a mound of stone to top, for the cor. of secs. 1 and 12 only, with brass cap mkd.
	T 31 N   T 31 N S 1   — R 69 E S 12   R 68 E   S 6 1936
	from which
	A juniper, 6 ins. diam., bears S. 61° W., 49 lks. dist., marked T 31 N R 68 E S 12 B T.
	A pine, 3 ins. diam., bears N. 44° W., 100 lks. dist., marked B T.
	Land, broken hills. Soil, rocky clay, 4th. rate. Timber, scattering pine and juniper; undergrowth, sagebrush and rabbit brush.
	North, on E. bdy. of sec. 1.
	Over rolling mountainous land, through scattering timber.
3.00	Ridge, bears E. and W.; descend 154 ft. over N. slope.
6.50	Road, bears N. 65° E., and S. 65° W.
17.70	Gulch, course E.; ascend 94 ft. over broken S. slope.
32.70	Spur, slopes E.; continue ascent 46 ft. along E. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to bedrock, with granite stone 6x6x6 ins. marked X deposited at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of sec. 1 only, with brass cap mkd.
	$\frac{1}{4}$   S 1   1936
	Ascend 24 ft. over broken S. slope.