


SUBDIVISION OF T. 31 N., R. 69 E.

Chains.

- 30.58 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, to bedrock, with a granite stone 9x7x7 ins., marked X deposited at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap marked



Descend 61 ft. over broken NW. slope.

- 46.58 Wash, course N. 25° E.; continue descent 46 ft. over rolling bottom.


- 70.58 The cor. of secs. 29, 30, 31 and 32.

Land, rolling.
Soil, rocky and gravelly clay, 4th. rate.
Timber, scattering pine and juniper; undergrowth, bunch grass, sagebrush and rabbit brush.

West, on a sectional correction line, bet. secs. 30 and 31

Over rolling mountainous land, through scattering timber and medium dense undergrowth; ascend SE. slope 97 ft.

- 15.95 Spur, slopes NE.; descend 7 ft. over NW. slope.
22.35 Bottom of descent, bears NE. and SW.; ascend 27 ft. over E. slope.
30.30 Spur, slopes N.; descend 20 ft. over broken W. slope.
40.00 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, to bedrock, with a limestone 7x7x7 ins., marked X deposited at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap marked



Descend 10 ft. over broken land.

- 45.30 Wash, course NE.; ascend 207 ft. over SE. slope.

- 77.30 Spur, slopes NE.; descend 7 ft. over NW. slope.

- 79.81 Intersect W. bdy. of Tp.

Set an iron post, 3 ft. long, 2 ins. diam., 6 ins. in the ground, to bedrock, with a granite stone 8x8x6 ins., marked X deposited at base, and in a mound of stone to top, for closing cor. of secs. 30 and 31, with brass cap marked