


SUBDIVISION OF T. 31 N., R. 69 E.

Chains.

West, on true line, bet. secs. 19 and 30.

Over rolling land, through scattering timber and dense undergrowth; ascend 130 ft. over broken E. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground, to bedrock, with a limestone 9x7x7 ins., marked X deposited at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap marked



Ascend 128 ft.


48.90 Ungraded road, bears NW. and SW.

62.45 Top of ascent, bears N. and S.; descend 15 ft.

69.15 Wash, course N. 65° E.; ascend 44 ft. along N. side of wash.

79.70 Intersect W. bdy. of Tp.

Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground, to bedrock, with a limestone 8x6x5 ins., marked X deposited at base, and in a mound of stone to top, for closing cor. of secs. 19 and 30, with brass cap marked



From this point the cor. of secs. 24 and 25 only, heretofore described, bears N., 11.12 chs. dist.

Land, rolling hills.

Soil, rocky and gravelly clay, 4th. rate.

Timber, scattering pine and juniper; undergrowth, sagebrush, rabbit brush and bunch grass.

South, on a blank line, along W. bdy. of sec. 30.

28.88 The $\frac{1}{4}$ sec. cor. of sec. 25 only, heretofore described.

40.03 Midpoint bet. closing cors. of secs. 19 and 30 and secs. 30 and 31.

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in the ground, to bedrock, with a limestone 7x7x5 ins., marked X deposited at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor. of sec. 30 only, with brass cap marked

