

SUBDIVISION OF T. 31 N., R. 69 E.

Chains.

S 17
 $\frac{1}{4}$ —————
 S 20
 1936

raise a mound
of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
Ascend 208 ft. over broken NE. slope.

79.78 The cor. of secs. 17, 18, 19 and 20.

Land, rolling.
 Soil, rocky and gravelly, 4th. rate.
 Timber, none; undergrowth, sagebrush and bunch grass.

West, on true line, bet. secs. 18 and 19.

Over rolling land, through medium dense undergrowth.

9.60 Ungraded road, bears NE. and SW.; ascend 83 ft. over broken E. slope.

31.90 Top of ascent, bears N. and S.; descend gradually over SW. slope.

39.95 Gulch, course NE.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

S 18
 $\frac{1}{4}$ —————
 S 19
 1936

raise a mound
of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
Ascend 51 ft. over broken NE. slope, through scattering timber.

79.59 Intersect W. bdy. of Tp.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for closing cor. of secs. 18 and 19, with brass cap marked

T 31 N
 R 68 E R 69 E

S 24 | S 18
 ———— C C
 S 19

1936

raise a mound
of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.

From this point, the cor. of secs. 13 and 24 only, heretofore described, bears N., 11.07 chs. dist.