SUBDIVISION OF T. 31 N., R. 69 E.

Chains	
39.93	Set an iron post, 3 ft. long, 1 in. diam., 3 ins. in the ground to bedrock, with a limestone 9x8x5 ins., mkd. X deposited at base, and in a mound of stone to top, for ¼ sec. cor., with brass cap mkd. ¼ S 5 / S 8 1936 Ascend 35 ft. over rocky E. slope.
40.05	Limestone ledge, 10 ft. high, bears N. for 50 lks. and S.
41.86	Wash, course S. 80° E.
43.35	Top of ascent, bears NW. and SE.; road bears NW. and SE.; descend 15 ft. along broken S. slope.
56.00	Bottom of descent, bears NW. and SE.; ascend 150 ft. over NE. slope.
78.00	Thence along N. slope.
79.86	The cor. of secs. 5, 6, 7, and 8. Land, rocky, rolling mountainous. Soil, rocky and gravelly; 4th. rate. Timber, scattering juniper; undergrowth, sagebrush.
	West, on true line, bet. secs. 6 and 7. Over rolling mountainous land, through medium dense undergrowth; ascend 25 ft. over E. slope.
4.45	Top of ascent, bears NW. and SE.; descend 65 ft. over SW. slope.
14.20	Wash, course SE.; road in bottom of wash, bears NW. and SE.; ascend 65 ft. over broken NE. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for ¼ sec. cor., with brass cap mkd. ¼ S 6 / S 7 1936 raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor. Ascend 98 ft. over broken NE. slope.
79.39	Set an iron post, 3 ft. long, 2 ins. diam., 20 ins. in the ground to bedrock, with a granite stone 8x7x6 ins. mkd. X deposited at base, and in a mound of stone to top, for closing cor. of secs. 6 and 7, with brass cap mkd. T 31 N R 68 E | R 69 E S 12 — S 6 / S 7 — C C 1936 From this point, the cor. of secs. 1 and 12 only, heretofore described, bears N., 11.15 chs. dist.