Chains	
	N. 89° 55' E., on a random line, bet. secs. 12 and 13.
40.00	Set temp. ¼ sec. cor.
80.08	Intersect the E. bdy. of the Tp., 9 lks. S. of the cor. of secs. 7, 12, 13, and 18; an iron post, 2 ins. diam., 8 ins. above ground, mkd. and witnessed, as described in the field notes of T. 32 N., R. 70 E., surveyed under this group.
	Thence
	S. 89° 51' W., on true line, bet. secs. 12 and 13.
	Asc. 50 ft. over nearly level land, on a gentle E. slope, thru scattering undergrowth.
2.10	Wash, course S.
19.50	U. S. Highway No. 50, bears N. 15° 13' E., and S. 15° 13' W.
21.70	Telephone Line, bears N. 15° E., and S. 15° W.
23.30	Road, bears N. 15° E., and S. 15° W.
26.20	Road, bears NE. and SW.
40.04	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for the ¼ sec. cor., with brass cap mkd. S12 / ¼ / S13 / 1937 raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.
45.20	Road, bears N. 60° W., and S. 60° E.
80.08	The cor. of secs. 11, 12, 13, and 14.
	Land, nearly level. Soil, rocky, sandy alkaline adobe, 3rd rate. No timber; undergrowth, sagebrush and greasewood.
	N. 0° 01' W., bet. secs. 11 and 12.
	Desc. 60 ft. over rolling land, along a NE. slope, thru scattering undergrowth.
26.00	Wash, course NE.
38.50	Wash, course N. 50° E.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for the ¼ sec. cor., with brass cap mkd. ¼ / S11 | S12 / 1937 raise a mound of stone, 5 ft. base, 2 ft. high, W. of cor.
45.30	Wash, course E.