

Chains

80.17 The cor. of secs. 3, 4, 9 and 10.

Land, level.
Soil, alkaline adobe, 4th rate.
No timber; undergrowth, greasewood.

ESTABLISHMENT OF $\frac{1}{4}$ -SECTION CORNERS ON NEVADA-UTAH
STATE BOUNDARY FOR T. 32 N., R. 70 E.

A point midway bet. the closing cor. for Tps. 31 and 32 N. R. 70 E., and the closing cor. for secs. 27 and 34, and S.0°16'W., 11.57 chs. dist., from Mile Post No. 50, herein before described.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for the $\frac{1}{4}$ sec. cor. for sec. 34, with brass cap mkd.

$\frac{1}{4}$ S34 |

1937

raise a mound
of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.

A point midway bet. the closing cor. of secs. 27 and 34, and the closing cor. of secs. 22 and 27, and S.0°18'W., 11.51 chs. dist. from Mile Post No. 49, hereinbefore described.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for the $\frac{1}{4}$ sec. cor. for sec. 27, with brass cap mkd.

$\frac{1}{4}$ S27 |

1937

dig pits,
18x18x12 ins., N. and S. of post, 3 ft. dist.

A point midway bet. the closing cor. of secs. 22 and 27, and the closing cor. of secs. 15 and 22, and S.0°18'W., 11.46 chs. dist. from Mile Post No. 48, hereinbefore described.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with a granite stone, 6x5x2 ins., mkd. X, deposited at base, for the $\frac{1}{4}$ sec. cor. for sec. 22, with brass cap mkd.

$\frac{1}{4}$ S22 |

1937

A point midway bet. the closing cor. of secs. 15 and 22, and the closing cor. of secs. 10 and 15, and S.0°18'W., 11.40 chs. dist. from Mile Post No. 47, hereinbefore described.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with a glass bottle containing a reproduction of brass cap deposited at base, for the $\frac{1}{4}$ sec. cor. of sec. 15, with brass cap mkd.