

204

Dependent Resurvey of 6th Standard Parallel N., thru R. 68 E.

Chains

N. 88° 43' W., on true line along the S. bdy. of sec. 36.

Asc. 60 ft. over rolling land, along a S. slope, thru scattering timber and undergrowth.

2.50 Road, bears N. 30° E. and S. 30° W.

9.00 Spur, slopes N., and W. 80° E.; desc. 70 ft. along a N. slope.

27.90 Draw, drains N. 65° E.; asc. 210 ft. along a S. slope.

40.01 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for the standard $\frac{1}{4}$ sec. cor., with brass cap mkd.

S C
 $\frac{1}{4}$ S 36

1938

raise a mound

of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.

48.50 Spur, slopes N. 65° E.; desc. 60 ft. over a W. slope.

58.40 Draw, drains N. 25° E.; asc. 370 ft. over an E. slope.

80.02 Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in the ground, to bedrock, with a granite stone, 5x5x3 ins. mkd. X, deposited at base, and in a mound of stone, 5 ft. base to top, for the standard cor. of secs. 35 and 36, with brass cap mkd.

S C
T31N R68E
S35 S36

1938

Land, rolling.

Soil, rocky clay; 3d rate.

Timber, scattering juniper and pine; undergrowth, sagebrush.

Grazing, fair.

N. 88° 43' W., on true line along the S. bdy. of sec. 35.

Asc. 30 ft. over rolling mountainous land, on an E. slope, thru scattering timber and dense undergrowth.

2.80 Top of ascent, bears N. and S.; desc. 90 ft. over a SW. slope.

8.20 Draw, drains S. 20° E.; asc. 610 ft. over a SE. slope.

17.40 Point of low spur, slopes S. 20° E.

23.10 Shallow draw, drains SE.

37.80 Spur, slopes SE.; over rolling land.

40.01 Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground, upon a cross (X) on bedrock, and in a mound of stone, 4 ft. base, to top, for the stand. $\frac{1}{4}$ sec. cor., with brass cap mkd.

S C
 $\frac{1}{4}$ S 35

1938

41.70 W. face limestone cliff, bears N. 30° W. and S. 30° E.; desc. 120 ft. abruptly.

44.70 Foot of cliff, bears N. 30° W. and S. 30° E.; draw, drains S. 30° E.; asc. 580 ft. over a SE. slope.