

222

Subdivision of T. 31 N., R. 68 E.

Chains	
	S. 89° 56' W., on true line bet. secs. 1 and 12. Asc. 280 ft. over rolling land along a S. slope, thru scattering timber and undergrowth.
15.70	Head of draw, drains S. 85° E.
24.90	Road, bears N. 75° E. and S. 25° W.; continue the ascent over an E. slope.
32.40	Draw, drains N. 10° E.; continue the ascent along a N. slope.
39.93	Set an iron post, 3 ft. long, 1 in. diam., 29 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.
	S 1 $\frac{1}{4}$ — S 12 1938
	raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
69.20	Desc. 60 ft. over W. slope.
77.10	Drain, course N.; asc. 30 ft. over a N. slope.
79.86	The cor. of secs. 1, 2, 11 and 12. Land, rolling. Soil, rocky clay; 3d rate. Timber, juniper and pine; undergrowth, sagebrush, shadscale and buttonbrush. Grazing, fair.
	N. 0° 01' W., on a random line bet. secs. 1 and 2.
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.14	Intersect the N. bdy. of the Tp., 26 lks. E. of the cor. of secs. 1, 2, 35 and 36; an iron post, 2 ins. diam., 7 ins. above ground, mkd. and witnessed as described in the field notes of the survey of T. 32 N., R. 68 E.
	Thence
	S. 0° 12' E., on true line, bet. secs. 1 and 2. Asc. 30 ft. over rolling land, on a N. slope, thru scattering timber and undergrowth.
.90	Point of spur, slopes SE.; desc. slightly over a S. slope.
2.90	Draw, drains E.; asc. slightly over a N. slope.
6.30	Draw, drains N. 40° E.; asc. 320 ft. over a NW. slope.
29.00	Spur, slopes N. 65° W.; desc. 90 ft. along a W. slope.
40.14	Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the ground to bedrock and in a mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S2 S1 1938
	from which