

276

NORTH BDY. OF T. 26 N., R. 54 E.

Chains
 21.80 Road, bears N. 25° E. and S. 30° W.
 24.30 Wash, course S.
 33.80 Road, bears NW. and S. 50° E.
 36.30 Shallow draw, drains N. 10° W.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with a quart of charcoal deposited at base, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

S 32
$\frac{1}{4}$
S 5
1939

From this cor., a standard U. S. Geological Survey bench mark, mkd. U. S. Geological Survey B.M. H-11 1936 5872 Elevation bears S. 63° 31' E., 14.83 chs. dist.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with a quart of charcoal deposited at base, for the cor. of secs. 5, 6, 31 and 32, with brass cap mkd.

T27N	R54E
S31	S32
S 6	S 5
T26N	
1939	

Land, nearly level flat.
 Soil, sandy clay; 2nd rate.
 No timber; undergrowth, sagebrush.
 Grazing, good.

S. 89° 46' W., on true line bet. secs. 6 and 31.

Over nearly level land, with slight slope to S., thru scattering undergrowth.

30.55 The cor. of Tps. 26 and 27 N., Rs. 53 and 54 E., an iron post, 3 ins. diam., 12 ins. above ground, firmly set, mkd. and witnessed as described in the official record. This cor. will hereafter refer to Tps. 27 N., Rs. 53 and 54 E. I alter the markings on the cor. monument to read as follows:

T 27 N	
R53E	R54E
S36	S31
T26N	R54E

1926

raise a mound

of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.

Destroy all evidence of the orig. cor. accessory.

Land, flat.
 Soil, sandy clay; 3d rate.
 No timber; undergrowth, sagebrush.
 Grazing, fair.

RESURVEY OF A PORTION OF THE 5TH STANDARD PARALLEL N., THRU RANGE
 54 EAST.

This line was independently resurveyed in 1921 under Group 94,