

SUBDIVISION OF T. 26 N., R. 54 E.

Chains

From the standard cor. for secs. 35 and 36, on the S. bdy. of the Tp.; an iron post, 2 ins. diam., 12 ins. above ground, mkd. and witnessed as described in the official record.

N. $0^{\circ} 01'$ W., bet. secs. 35 and 36.

Desc. 60 ft. over mountainous land, on a N. slope, thru scattering timber and undergrowth.

5.90 Draw, drains W.; asc. 120 ft. over a S. slope.

20.00 Top of ascent, bears E. and W.; desc. 320 ft. over a N. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
S35 | S36

1939

raise a mound
of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

62.80 Spur, slopes S. 80° W.; desc. 280 ft. over a N. slope.

74.70 Gulch, course N. 70° W.; asc. 100 ft. over a SW. slope.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground, over a cross (X) on bedrock, and in a mound of stone to top, for the cor. of secs. 25, 26, 35 and 36, with brass cap mkd.

T26N R54E
S26 | S25

S35 | S36

1939

Land, mountainous.

Soil, rocky clay; 3d rate.

Timber, pine and juniper; undergrowth, sagebrush.

Grazing, fair.

East, on a random line bet. secs. 25 and 36.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

79.80 Intersect the E. bdy. of the Tp., 28 lks. N. of the cor. for secs. 25 and 36, an iron post, 2 ins. diam., 10 ins. above ground, mkd. and witnessed as described in the official record.

Thence

N. $89^{\circ} 48'$ W., on true line bet. secs. 25 and 36.

Asc. 320 ft. over mountainous land, on a SE. slope, thru scattering timber and undergrowth.

14.40 Draw, drains S. 80° E.; leave scattering timber; continue the ascent over an E. slope.

39.90 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

S 25
 $\frac{1}{4}$

S 36

1939

raise a mound
of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.