

SUBDIVISION OF T. 27 N., R. 54 E.

Chains
39.98

Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground, to bedrock, and in a mound of stone to top, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{r} S\ 3 \\ \frac{1}{4} \\ \hline S\ 10 \\ 1939 \end{array}$$

from which

A juniper, 6 ins. diam., bears N. 80° E., 94 lks. dist., mkd.
 $\frac{1}{4}$ S 3 B T.

A juniper, 12 ins. diam., bears S. 80° E., 166 lks. dist., mkd.
 $\frac{1}{4}$ S 10 B T.

From this $\frac{1}{4}$ sec. cor., a high rocky peak, bears N. 86° 10' E., 8.82 chs. dist.

50.40

Drain, course N. 25° W. from S. 70° E., asc. 90 ft. over a NE. slope.

73.50

Leave NE. slope; continue ascent along a N. slope.

79.96

The cor. of secs. 3, 4, 9 and 10.

Land, rolling mountainous.

Soil, rocky clay; 3d and 4th rate.

Timber, juniper; undergrowth, sagebrush and mountain grasses.

Grazing, poor to good.

N. 0° 02' W., on true line, bet. secs. 3 and 4.

Desc. 110 ft. over rolling mountainous land, on a N. slope, thru scattering timber and undergrowth.

17.20

Draw, drains N. 80° E.; asc. 230 ft. over a SE. slope.

34.00

Leave SE. slope, continue ascent along an E. slope.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 17 ins. in the ground to bedrock, with a basalt stone, 6x4x4 mkd. with a cross (X) deposited at base, and in a mound of stone to top for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{r} \frac{1}{4} \\ S4\ | \ S3 \\ 1939 \end{array}$$

From this $\frac{1}{4}$ sec. cor., a conical peak, bears N. 17° 16' W., 16.78 chs. dist.

61.00

Low spur, slopes N. 70° E.; desc. 250 ft. over a NE. slope.

66.00

Leave NE. slope; continue to desc. over a N. slope.

78.84

Intersect the N. bdy. of the Tp.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for the closing cor. for secs. 3 and 4, with brass cap mkd.

$$\begin{array}{r} T28N\ R54E \\ S\ 34 \\ \hline S4\ | \ S3 \\ T27N\ R54E \\ CC \\ 1939 \end{array}$$

from which