

SUBDIVISION OF T. 27 N., R. 54 E.

Chains	
79.96	Intersect the N. and S. line, 2 lks. N. of the cor. of secs. 3, 4, 9 and 10.
	Thence
	S. 89° 43' W., on true line, bet. secs. 4 and 9.
	Desc. 30 ft. over rolling land, along a N. slope, thru scattering undergrowth.
14.50	Road, bears N. 20° W. and S. 30° W.; foot of descent, bears N. and S.; asc. 90 ft. over a E. slope.
35.00	Low ridge, bears N. 70° W. and S. 70° E.; continue to asc. 60 ft. along a S. slope.
39.98	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with a quart of charcoal deposited at base, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} S\ 4 \\ \hline \frac{1}{4} \\ S\ 9 \\ 1939 \end{array}$
79.96	The cor. of secs. 4, 5, 8 and 9.
	Land, rolling.
	Soil, sandy rocky clay; 3d rate.
	No timber; undergrowth, sagebrush.
	Grazing, fair.
	N. 0° 03' W., on true line, bet. secs. 4 and 5.
	Desc. 110 ft. over mountainous land, on a N. slope, thru scattering timber and undergrowth.
7.00	Foot of descent, bears E. and W.; top of rocky knoll, bears E.; 8.00 chs. dist.; asc. 170 ft. over a SW. slope.
33.00	Ridge, bears N. 80° W. and S. 80° E.; desc. 180 ft. over a N. slope.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ S5 \quad \quad S4 \\ 1939 \end{array}$
	raise a mound
	of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.
56.10	Wash, course N. 70° E.; over nearly level land.
58.00	Draw, drains N. 75° E.; asc. 80 ft. over a S. slope.
70.00	Spur, slopes N. 70° E.; desc. 60 ft. over a N. slope.
78.00	Draw, drains N. 80° E.; over nearly level land.
79.27	Intersect the N. bdy. of the Tp.
	Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for the closing cor. for secs. 4 and 5, with brass cap mkd.