

429

COMPLETING THE SUBDIVISION OF PARTIAL T. 26 N., R. 55 E.

Chains

40.00

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S18

$\frac{1}{4}$

S19

1936

raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N. of cor.

Asc. 230 ft. over broken E. slope.

65.50

Top of spur projects NE.; desc. 10 ft.

71.80

Wash, course N. 60° E.; asc. 170 ft.

80.82

Intersect the W. bdy. of the Tp.

Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for the closing cor. of secs. 18 and 19, with brass cap mkd.

T26N	T26N	
R54E	S18	
		CC
S13	S19	
	R55E	
	1936	

raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high E. of cor.

From this point the cor. of secs. 13 and 24, T. 26 N., R. 54 E., heretofore described, bears S. 2.09 chs. dist.

Land, rolling mountainous.

Soil, light sandy clay loam, mixed with adobe, alkali and coarse gravel and volcanic rock.

Timber, none.

Undergrowth, sagebrush.

At midpoint, bet. the closing sec. cors. on W. bdy. sec. 19,

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 19 only, with brass cap mkd.

$\frac{1}{4}$ S19
1936

From this point, the $\frac{1}{4}$ sec. cor. on E. bdy., sec. 24, T. 26 N., R. 54 E., heretofore described, bears South, 2.09 chs. dist.

From the cor. of secs. 17, 18, 19, and 20.

N. 0° 01' W., bet. secs. 17 and 18.

Over rolling mountainous land, through dense undergrowth; desc. 70 ft. over a gentle NE. slope.