

COMPLETING THE SUBDIVISION OF PARTIAL T. 26 N., R. 55 E.

Chains

39.93. Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S 8

$\frac{1}{4}$ —————

S 17

1936

raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, N. of cor.

52.40 Wash, 180 ft. below $\frac{1}{4}$ sec. cor., course N. 20° W.; desc. 120 ft. over NW. slope.

79.86 The cor. of secs. 7, 8, 17 and 18.

Land, rolling mountainous.

Soil, shallow sandy clay mixed with adobe, coarse gravel, and volcanic rocks.

Timber, scrub juniper and pinon.

Undergrowth, sagebrush and rabbit brush.

West, on a true line bet. secs. 7 and 18.

Over rolling mountainous land, through dense undergrowth; desc. 20 ft.

6.70 Wash, 10 lks. wide, 2 ft. deep, course N. 30° E.; asc. 30 ft. over gentle E. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground, for $\frac{1}{4}$ sec. cor, with brass cap mkd.

S 7

$\frac{1}{4}$ —————
S18

1936

raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, N. of the cor.

Asc. 40 ft. over gentle E. slope.

64.50 Begin slightly steeper ascent over E. slope of top of small spur 40 ft. to cor.

80.77 Intersect the W. bdy. of the Tp.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for the closing cor. of secs. 7 and 18, with brass cap mkd.

T26N	T26N
R54E	S7 CC
S12	S18
	R55E
	1936

raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, E. of cor.

From this point the cor., of secs. 12 and 13, on E. bdy. T. 26 N., R. 54 E., heretofore described, bears South, 2.04 chs. dist.