


COMPLETING THE SUBDIVISION OF PARTIAL T. 26 N., R. 55 E.

Chains

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor. for sec. 6 only, with brass cap mkd.



1936

raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.

From this $\frac{1}{4}$ sec. cor., the cor. of Tps. 26 and 27 N., Rs. 54 and 55 E., heretofore described, bears North, 40.55 chs. dist.

From the cor. of secs. 5, 6, 7, and 8.

N. 0° 01' W., ^{on true line} /bet. secs. 5 and 6.

Over rolling mountainous land, through dense undergrowth; asc. 5 ft.

2.30 Point of low spur, projects N. 80° W.; desc. 10 ft.

8.30 Wash, course W.

12.30 Wash, course W.

19.30 Wash, course N. 10° W.

21.30 Enter scattering timber, bears E. and W.

28.00 Large deep wash, course W.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.



1936

raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$ ft. high, W. of cor.

Desc. 31 ft. over rolling land to N. bdy.

44.50 Large deep wash, course N. 5° W.

57.40 Wash, course W.

66.00 Leave timber, bears N. 25° W. and S. 25° E.

76.30 Wash, course N. 10° W.

77.00 Enter scattering timber, bears E. and W.

80.52 Intersect N. bdy. of Tp.

At the point of intersection.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for closing cor. of secs. 5 and 6, with brass cap mkd.