

DEPENDENT RESURVEY OF SUBDIVISIONAL LINES T. 28 N., R. 55 E.

Chains

ground, with original cor. monument deposited alongside, for the cor. of secs. 1, 2, 11 and 12, with brass cap mkd.

T28N	R55E
S 2	S 1
S11	S12

1939

Land, nearly level and slightly rolling.
Soil, sandy clay, 2nd and 3d rate.
No timber; undergrowth, sagebrush, rabbitbrush and native grasses.
Grazing, good to fair.

N. 6° 53' W., on true line bet. secs. 2 and 3.

Desc. 40 ft. over rolling land, on a NE. slope, thru scattering undergrowth.

8.30 Foot of descent, bears N. and S. 20° E.; asc. 30 ft. over broken land.

41.99 Proportionate distance. No trace of old cor. found.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for the $\frac{1}{4}$ sec. cor. for sec. 2 only, with brass cap mkd.

	$\frac{1}{4}$ S 2
--	-------------------

1939

raise a mound

of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, E. of cor.

80.70 Road, bears N. 80° E. and S. 80° W.

83.50 The cor. of secs. 2, 3, 34 and 35, on N. bdy. of Tp.

Land, rolling.
Soil, sandy, rocky clay; 3d rate.
No timber; undergrowth, sagebrush.
Grazing, fair.

SUBDIVISION OF T. 28 N., R. 55 E.

From the cor. of secs. 9, 10, 15 and 16,

North, on a Sectional Guide Meridian, bet. secs. 9 and 10.

Desc. 20 ft. over rolling land, on a N. slope, thru scattering undergrowth.

10.00 Drain, course E.; asc. 80 ft. over a S. slope.

40.00 Top of ascent, bears E. and W.; desc. 90 ft. over a N. slope.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with a quart of charcoal deposited at base, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

S9		S10
----	--	-----

1939

75.60 Draw, drains E.; over broken land.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground,