

SUBDIVISION OF T. 28 N., R. 55 E.

Chains

raise a mound  
of stone, 2 ft. base, 1½ ft. high, W. of cor.

The ¼ sec. cor. on W. bdy. of Sec. 2, bears N. 6° 53' W., 3.25 chs. dist.

From the cor. for secs. 3, 4, 9 and 10.


North, on a sectional guide meridian, bet. secs. 3 and 4.

Asc. 160 ft. over rolling land, on a S. slope, thru scattering undergrowth.

4.80 Road, bears N. 70° W. and S. 70° E.

39.50 Wash, course S. 80° E.


40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with a quart of charcoal deposited at base, for the ¼ sec. cor., with brass cap mkd.



56.00 Road, bears N. 65° E. and S. 65° W.

83.91 Intersect the N. bdy. of the Tp.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with a quart of charcoal deposited at base, for the closing cor. of secs. 3 and 4, with brass cap mkd.



From this point the cor. for secs. 33 and 34, bears S. 89° 38' W., 9.90 chs. dist.

Land, rolling.  
Soil, sandy clay; 3d rate.  
No timber; undergrowth, sagebrush and rabbitbrush.  
Grazing, fair.

From the cor. for secs. 20, 21, 28 and 29,

North, on a sectional guide meridian, bet. secs. 20 and 21.

Desc. slightly over rolling, broken land, on a N. slope, thru scattering undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with a quart of charcoal deposited at base, for the ¼ sec. cor., with brass cap mkd.

