

549

SUBDIVISION OF T. 42 N., R. 65 E.

Chains

T42N	R65E
S19	S20

S29

1938

raise a mound
of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

81.62 The corner of secs. 29 and 30, only, hereinbefore described.

Land, rolling.

Soil, sandy clay, 2nd rate.

Timber, none; undergrowth, sagebrush.

Grazing, poor.

From the cor. of secs. 29 and 30 only,

West, on true line, along the N. bdy. of sec. 30.

Asc. 110 ft. over rolling land, along a SE. slope, thru scattering undergrowth.

29.60 Leave rolling land, asc. 190 ft. over rolling mountainous land.

37.70 Spur, slopes SE.; over broken land.

38.38 Set an iron post, 3 ft. long, 1 in. diam., upon a cross (X) on bedrock, and in a mound of stone 5 ft. base to top, for the $\frac{1}{4}$ sec. cor. for sec. 19, with brass cap mkd. $\frac{1}{4}$ S 19

1938

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor. for sec. 30, only, with brass cap mkd. $\frac{1}{4}$ S 30

1938

raise a mound
of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of cor.

51.20 Draw, drains S. 70° E.; asc. 40 ft. along a N. slope.56.50 Draw, drains S. 75° E.; continue to asc. 400 ft. along a N. slope.

78.14 Intersect the W. bdy. of the Tp.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for the closing cor. for secs. 19 and 30, with brass cap mkd.

T42N		
R64E	R65E	
	S19	
S25	S30	CC

1938

raise a mound
of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.

From this point the cor. of secs. 24 and 25, T. 42 N., R. 64 E., hereinbefore described bears N. $0^\circ 38'$ E., 5.17 chs. dist.