

Dependent Resurvey of the N. Bdy., T. 4 N., R. 66 E.
with establishment of cors. at regular intervals for T. 5 N., R. 66 E.

Chains

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T5N R66E

¼ S 6
T4N
1957

Bury the original corner stone alongside the iron post.

from which

A juniper, 24 ins. diam., bears S. 69° W., 25 lks. dist., mkd.
¼ S6 BT.

N. 89° 49' W., beginning new measurement.

Continue ascent; asc. 110 ft. over broken, general ENE. slope.

14.00 Crest of spur, slopes NE.

29.10 Wash, 10 lks. wide, 2 ft. deep, drains NE.

29.58 Point for the 1/16 sec. cor. of sec. 31, T. 5 N., R. 66 E.

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T5N R66E

1/16 S31 .80.00
T4N
1957

from which

A juniper, 8 ins. diam., bears N. 60° E., 36 lks. dist., mkd.
1/16 S31 BT.

Note: Wash, 10 lks. wide, 2 ft. deep, drains ENE., 30 lks. S. of cor.

Continue ascent; asc. 35 ft. over ENE. slope to corner point

37.69 The cor. of Ts. 4 and 5 N., Rs. 65 and 66 E., which is monumented with a 3 in. iron post, set, mkd. and witnessed as described in the official record of the 1919 survey, T. 5 N., R. 65 E., by J. C. Clark.

Land, rolling hills, general E. to ENE. drainage.

Soil, rocky and gravelly.

Timber, heavy juniper.

Undergrowth, dense sagebrush.

Independent Resurvey of a Portion of the Subdivision, T. 5 N., R. 66 E.

Superseding the original survey by
Monroe and Bateman, Deputy Surveyors, in 1872 and 1873

Beginning at the cor. of secs. 35 and 36 on the S. bdy. of the township, a 2½ in. iron post, hereinbefore described.