

## Dependent Resurvey East Boundary of T. 26 N., R. 51 E.

## Chains

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with the original cor. monument deposited at base, for the cor. of secs. 1 and 12, with brass cap mkd.

T 26 N	T 26 N
S 1	R 52 E
S 12	
R 51 E	S 7
1939	

raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Land, rolling.

Soil, rocky clay, 3d rate.

Timber, scattering juniper; undergrowth, sagebrush.

Grazing, fair.

N.  $0^{\circ} 22'$  E., on true line, along the E. bdy. of sec. 1.

Desc. 40 ft. over rolling land, along a W. slope, thru scattering timber and undergrowth.

2.13 Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground for the cor. of secs. 6 and 7, with brass cap mkd.

T 26 N	T 26 N
R 51 E	S 6
	S 7
S 1	R 52 E
1939	

raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, E. of cor.

31.70 Spur, slopes NW.; desc. 60 ft. over a broken N. slope.

39.85 Point for the  $\frac{1}{4}$  sec. cor. of sec. 1, only.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for the  $\frac{1}{4}$  sec. cor. of sec. 1, with brass cap mkd.

$\frac{1}{4}$  S 1  
1939

raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

42.13 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for the  $\frac{1}{4}$  sec. cor. of sec. 6, with brass cap mkd.

$\frac{1}{4}$  S 6  
1939

raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, E. of cor.

42.70 Draw, course N.  $55^{\circ}$  W., asc. 40 ft.

51.70 Spur, slopes NW., desc. 100 ft.

65.00 Draw, drains NW.; over broken land.

79.70 The cor. of Tps. 26 and 27 N., Rs. 51 and 52 E.; a cedar post,  $3\frac{1}{2}$  ins. sq., 42 ins. above ground, mkd. with 6 grooves on each side.

At point for cor.