

Dependent Resurvey of a
Portion of South Boundary, T. 27 N., R. 52 E.

- Chains Desc. 100 ft. over rolling land, along a NW. slope, thru scattering timber and undergrowth.
- 13.40 Draw, drains N. 60° W.; continue to desc. 110 ft. along a N. slope.
- 38.50 Draw, drains NW.; over nearly level land, in bottom of draw.
- 39.52 The $\frac{1}{4}$ sec. cor. of secs. 6 and 31; a cedar post, 2 ins. sq., 40 ins. above ground, in a mound of stone, and mkd. $\frac{1}{4}$. This $\frac{1}{4}$ sec. cor. will hereafter refer to sec. 31, only.
- At point for cor.
- Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with the original cor. monument deposited alongside, for the $\frac{1}{4}$ sec. cor. of sec. 31, with brass cap mkd.
- $\frac{1}{4}$ S 31
- 1939.
- No suitable accessory.
- Thence S. 89° 43' W.
- 3.70 Wash. course NW.; asc. 60 ft. along a SE. slope.
- 28.20 Top of ascent, bears NW. and SE.; desc. 40 ft. over a broken W. slope.
- 39.84 The cor. of Tps. 26 and 27 N., Rs. 51 and 52 E.
- Land, rolling and broken.
Soil, rocky clay, 3d rate.
Timber, scattering pine and juniper; undergrowth, sagebrush.
Grazing, fair.

Dependent Resurvey of Subdivisional Lines,
T. 26 N., R. 52 E.

- Reestablishment of survey executed by O.A. Palmer, Deputy Surveyor, 1870.
- From the Stan. Cor. of secs. 32 and 33, on S. bdy. of Tp. N. 1° 48' E., on true line, bet. secs. 32 and 33.
- Desc. slightly over rolling land, along a W. slope, thru scattering timber and undergrowth.
- 2.80 Wash, course W.; asc. slightly.
- 25.80 Wash, course S. 75° W.; asc. 40 ft. along a W. slope.
- 34.30 Fence, bears NW. and SE.
- 40.02 Proportional distance for the $\frac{1}{4}$ sec. cor.; no trace of the original cor. monument was found.
- Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
S 32 | S 33
1939

from which