

Chains

$\frac{1}{4}$ S 4 |
1939

No suitable accessory.

From this point the $\frac{1}{4}$ sec. cor. of sec. 3, bears S. 0° 14' E., 1.42 chs. dist.

From the cor. of secs. 4, 5, 8, and 9.

North, on a sectional guide meridian, bet. secs. 4 and 5.

Desc. 50 ft. over rolling land, on a NW. slope, thru scattering timber and undergrowth.

19.90 Draw, drains W.; asc. 20 ft. over a S. slope.

26.60 Top of ascent, bears E. and W.; desc. 80 ft. over a broken NW. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

S 5 $\frac{1}{4}$ S 4
1939

raise a mound
of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.

44.70 Road, bears N. 75° E. and S. 75° W.

61.40 Drain, course N. 50° W.

70.00 Shallow draw, drains N. 80° W.

78.38 Intersect the N. bdy. of the Tp.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with a quart of charcoal deposited at base, for the closing cor. of secs. 4 and 5, with brass cap mkd.

T 27 N R 52 E
S 33
S 5 | S 4
T 26 N | R 52 E
CC
1939

No suitable accessory.

From this point the cor. of secs. 32 and 33, bears S. 89° 41' W., 6.47 chs. dist.

Land, rolling.

Soil, rocky clay, 3d rate.

Timber, scattering pine, juniper and cedar; undergrowth, sagebrush.

Grazing, good.

At a point N. 89° 41' E., 40.00 chs. dist. from the closing cor. of secs. 4 and 5.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for the $\frac{1}{4}$ sec. cor. of sec. 4, with brass cap mkd.