

SOUTH BOUNDARY OF T. 29 N., R. 53 E.

Chains

 $\frac{1}{4}$ S 34

1939

raise a mound

of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

- 76.87 The cor. of secs. 3 and 4; an iron post, 2 ins. diam., 9 inches above ground, mkd. and witnessed as described in the official record.
- 82.04 The cor. of secs. 33 and 34; an iron post, 3 ins. diam., 12 ins. above ground, mkd. and witnessed as described in the official record.

RESURVEY OF PORTION OF SUBDIVISION, T. 29 N., R. 53 E.

From the cor. of secs. 23 and 24, hereinafter described.

West, on true line bet. secs. 23 and 26.

I find the topography on the lines bet. secs. 23 and 26, and 22 and 27, to agree with the official record; therefore, it is omitted.

- 39.04 Point for the $\frac{1}{4}$ sec. cor. for sec. 26.
- Set an iron post, 3 ft. long, 1 in. diam., 15 ins. in the ground, upon a cross on bedrock and in a mound of stone to top, for the $\frac{1}{4}$ sec. cor. for sec. 26, with brass cap mkd.

 $\frac{1}{4}$ S 26

1939

- 40.00 The $\frac{1}{4}$ sec. cor. for secs. 23 and 26; an iron post, 1 in. diam., 12 ins. above ground, mkd. and witnessed as described in the official record; this $\frac{1}{4}$ sec. cor. will hereafter refer to sec. 23 only, and, therefore, I properly alter the markings upon the iron post to read as follows:

 $\frac{1}{4}$ S 23

1915

- 79.04 Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for the cor. for secs. 26 and 27, with brass cap mkd.

T29N R53E

S23

S27 | S26

1939

raise a mound

of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of cor.

- 80.00 The cor. for secs. 22, 23, 26 and 27; an iron post, 2 ins. diam., 12 ins. above ground, mkd. and witnessed as described in the official record. This cor. will hereafter refer to secs. 22 and 23 only; therefore, I properly alter the markings upon the iron post to read as follows:

T29N R53E

S22 | S23

1915

I destroy the accessory and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft high, N. of cor.