

DEPENDENT RESURVEY OF THE E. BDY. OF T. 45 N., R. 31 E.

Chains

Undergrowth, sagebrush, buck brush.
Grazing, good.

DEPENDENT RESURVEY OF SUBDIVISION OF T. 45 N., R. 32 E.

Dependent resurvey of a portion of the subdivision of T. 45 N., R. 32 E., reestablishing the survey executed by G. W. Garside and C. S. Preble, U. S. Deputy Surveyors, in 1875.

Extensive retracements and exhaustive search revealed no trace of the original corners within the township or of the original closing corners of secs. 2 and 3, or of secs. 3 and 4. The closing corners of secs. 2 and 3 and of secs. 3 and 4, were reestablished at record bearing and distance from the original standard corner of secs. 33 and 34, on the N. bdy., the nearest identified original corner. A line was run from the cor. of secs. 34 and 35, on the S. bdy., to the reestablished closing cor. of secs. 2 and 3, setting corners thereon at proportionate distance. Section corners were reestablished at record distance in departure from those reestablished corners and at record distance in latitude from the S. or N. boundaries as shown on the plat approved April 17, 1875. Quarter section corners were established at proportionate distance between the respective section corners.

Begin the dependent resurvey at the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., an iron post, 2 ins. diam., set, mkd. and witnessed as described in the official record.

N. 1° 10' E., along the W. bdy. of sec. 35.

Asc. 30 ft. over SE. slope.

2.20 Thence along E. slope.

17.60 Wash, course E.; continue along E. slope.

22.20 Thence desc. 90 ft. NE. slope.

36.90 Draw, drains E.; asc. southeasterly slope.

40.01 Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground, with a lava stone, 4x3x2 ins., mkd. X, deposited at base, and in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ S34
1938

42.365 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., over a X mkd. on surface rock, with a lava stone, 8x6x4 ins., mkd. X, at base, in a mound of stone to top, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ S35
1938

43.40 Spur, 50 ft. above draw, slopes E.; desc. 290 ft. over NE. slope.

63.00 Sidehill drain, course E.

65.50 Sidehill drain, course E.

79.00 Draw, drains E.; over valley floor.

80.02 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 27 and 34, with brass cap mkd.